

Unmanned Aerial Vehicle for Topographical Mapping of Inaccessible Land Areas in Ghana: A Cost-Effective Approach

**Naa Lamkai Quaye-Ballard, Daniel Asenso-Gyambibi and Jonathan Quaye-Ballard,
Ghana**

Key words: Unmanned Aerial Vehicle (UAV), Global Positioning System (GPS), Geographic Information System (GIS), Tailings Storage Facility (TSF), Ground Control Point (GCP)

SUMMARY

The use of Unmanned Aerial Vehicles (UAVs) for remote data acquisition has rapidly evolved in recent years. The integration of UAV with Global Positioning System (GPS) and Geographic Information System (GIS) techniques have reduced time and cost in acquiring data for inaccessible land areas. Topographical mapping of water bodies, marshy areas or land areas without land cover using traditional methods of surveying in Ghana is time consuming and challenging. This study considered topographical mapping of muddy Tailings Storage Facility (TSF) sites at a rain forest mining area at Osino in the Eastern Region of Ghana. DJI Phantom 4 Pro consumer UAV was flown at an altitude of 75m in a 3D flight mode. Real Time Kinematic (RTK) GPS was used to coordinate a reflective-marked Ground Control Point (GCP). Georeferencing the orthophoto was done using the GCP. Digital Terrain Model (DTM) was generated from the processed orthophotos after which contours at 5 m interval were generated. Cross sections across the TSF were drawn for further geotechnical and stability analysis for the tailings dam. The accuracy of the topographic map is below 5 cm and confirms the suitability of using consumer grade UAVs for topographical mapping of inaccessible areas in a cost-effective manner. Thus, the integration of RTK technology with the UAV and GIS is a feasible and appropriately accurate solution for mapping inaccessible areas.

Unmanned Aerial Vehicle for Topographical Mapping of Inaccessible Land Areas in Ghana: A Cost-Effective Approach

**Naa Lamkai Quaye-Ballard, Daniel Asenso-Gyambibi and Jonathan Quaye-Ballard,
Ghana**

1. INTRODUCTION

Topographical surveying is mostly required by Engineers and Architects to aid in infrastructural designs and construction. Topographical maps are used for planning, monitoring and development of infrastructure in Ghana. Geomatic Engineers are professionally required to undertake the topographic surveying in accordance with the code of ethics of the Ghana Institution of Surveyors (GhIS) and the standards from the Survey and Mapping Division (SMD) of the Lands Commission of Ghana. Due to the high cost of topographical surveying, unprofessional Surveyors are either hired or even not involved in infrastructural development and planning. This is evident in the haphazard infrastructural development in Ghana resulting in persistent flooding after rainfall and collapse of buildings especially in the urban areas like Accra, Kumasi. Professional land Surveyors in Ghana are constantly researching on cost effective methods of surveying in order to achieve Sustainable Development Goals (SDG) 9 and 11 (Terah Antwi et al., 2020). To undertake a topographical survey, considerations must be made on the purpose, map use, scale, size and terrain involved, cost, equipment to be used, duration and surveyor's experience (Ghilani & Wolf, 2012). General mapping surveying is done by either ground and photogrammetric methods or both (Ghilani & Wolf, 2012). The most common survey instruments in Ghana are the Total Station and Global Positioning System (GPS). Topographical mapping of water bodies, water-logged areas or land areas without land cover using traditional methods of surveying in Ghana is time consuming and challenging. To map out swampy areas, flooded areas or any area without getting in contact with the land surface have been daunting tasks with high cost of operation and risk to the surveyor. Photogrammetry methods, remote sensing data, scanners and LiDAR mapping have been the available accurate way of mapping such areas (Jalayer et al., 2015; Lato et al., 2015; Lim et al., 2003; Tang & Shao, 2015). These surveying methods are, however, very expensive to undertake.

The Land Surveying profession is constantly searching for fast and cost-effective ways of surveying inaccessible area for years (Casagli et al., 2017; Malehmir et al., 2016; Quaye-Ballard et al., 2013). In recent times, the use of UAVs in surveying is being practiced worldwide (Christiansen et al., 2017; Gonzalez et al., 2016; Turner et al., 2016). UAVs, specially built with on board high accuracy GPS and specifically built for mapping are available, but at a high cost. However, consumer grade UAVs which are cheaper, simple to use and easily available with multiple uses including photography, delivery, agriculture and surveillance, are being used with the aid of GPS and Ground Control Point (GCP) for topographical surveying (Aleshin et

al., 2019). UAVs survey uses photogrammetry methods with an output of orthophotos which are geo-referenced and further processed for geographic data with the aid of software. UAVs also used for vegetation cover estimation (e.g. Chen et al., 2016; Ghazal et al., 2015; Torres-Sánchez et al., 2014) as well as river topography and vegetation (Watanabe & Kawahara, 2016). Orthophotos give a pictorial view of the site which makes planning and analysis easier, unlike conventional surveying methods where sketches and pictures are taken in addition.

This type of UAVs for land surveying has proved to be accurate for topographical survey worldwide. For example, Chi *et al.* (2016) studied High Accuracy Topographic Mapping via UAV-based Images and identified the integration ability of high accuracy topographic map via the image of quad-rotors UAV and ground control points (GCPs) in Taiwan. Chi *et al.* concluded that UAV-based surveying may be good to replace current GPS and total station in the future. Sadikin *et al.* (2019) worked on “Topographic Mapping Using Unmanned Aerial Vehicle (UAV) Technology-Photogrammetry Method” in Indonesia and concluded that the produced topographic map meets the needs of a 1:1,000 and 1:2,000 in the horizontal and vertical directions respectively. Watanabe *et al.* (2016), evaluated the accuracy of Digital Surface Model (DSM) of river-channel morphology derived from the imagery acquired with a low-cost digital camera on board an unmanned multi-copter. The study concluded that DSM from UAV based photogrammetry technique reproduces the ground elevation very well with the maximum error of 4 cm over a floodway where the vegetation height and density are low and that the DSM reasonably captures the thick vegetation cover over sandbars. Obanawa *et al.* (2015) in “High-resolution topographic survey using small UAV and SfM-MVS technologies in hardly accessible area” in Japan concluded that it is possible to survey the inaccessible area like free face and deep gorge in detail. Fitzpatrick (2015) found that using UAVs for volumetric calculation and topographic mapping is as accurate as traditional survey methods and mostly cost and time effective when mapping areas 10 to 200 acres in size at locations with little or no vegetation. Aleshin *et al.* (2019) used Phantom 4 UAV in creating DTM and presented the qualitative comparison of DTM that were generated using different engineering equipment and various processing methods. The analysis of the results was based on the least squares method. The study concluded that the use of the photos from the UAVs is effective for the DTM generation. Taddia *et al.* (2019) conducted research in Italy by using DJI phantom 4 Real Time Kinematic (RTK) UAV for topographic mapping of coastal areas and confirmed that the on-board RTK approach really speeds up the precise mapping of coastal regions and that a single GCP may be needed to make a reliable estimation of the focal length.

This study examines the suitability and accuracy of a topographical survey conducted with the combination of RTK-GPS instrument and a consumer grade UAV at an inaccessible tailings dam at Osino in the Eastern Region of Ghana to produce cross sections and contours for design and construction of tailings storage facility (TSF). TSF are earth-filled embankment dam that are used to store byproducts of mining operation (Choi & Song, 2016; Wang, 2017; Yakubu et al., 2019). Mining areas located at Osino and Asiakwa in the Eastern Region of Ghana are within the valley flats of the Birim sub-basin of the Pra River. The region is dominated with heavy rainfall during the rainy seasons in Ghana. Due to the fact that TSFs are earth-filled, heavy rainfall renders the dam walls weak, muddy and inaccessible. An unstable TSF may collapse and cause environmental pollution, loss of life and property Wang (2017).

Geotechnical investigation and stability analysis test are periodically done in order to check the condition of the dams, redesign and reconstruct to improve productivity and safety (Attewill et al., 2004; Brown & Hewitt, 2016; Dong et al., 2019). TSF geotechnical investigations require a topographical survey with Digital Terrain Model (DTM) and contours for generating cross sectional drawings of the dam for stability analysis test (Pastor et al., 2015; Torgoev, 2017).

2. METHODOLOGY

The methods and data process adopted for the study is shown in Figure 1.




Figure 1: Flowchart of methods and data processing

2.1 Reconnaissance Survey

A site visit was done to plan the best way to undertake the studies. The Survey and Mapping Division (SMD) of the Lands Commission of Ghana was visited to seek locations and coordinates of National benchmarks closer to the study location. A desk study was done by studying Google and Topographical maps of Ghana.

2.2 Establishment of Benchmarks and GCP

From National benchmarks provided by the SMD, a total of four concrete Temporal Benchmarks (TBM) were established using static GPS surveying method. A vehicle screen shield which costs less than a dollar together with a masking tape was used as a reflective material for GCP (Figure 2). Six GCPs were established near the tailings dam via static GPS surveying method.




Figure 2: (a) Team constructing reflective material ; and (b) Reflective material used as GCP

2.3 GPS- RTK Survey

RTK-GPS survey was carried out in a semi-kinematic or the stop-and-go mode to improve the accuracy of data of geographic details at locations that were easily accessible by the team (Figure 3). Spot heights across the TSF at notable locations were also taken. Two (2) points were taken on reflective materials to be used as validating points.



Figure 3: GPS-RTK Survey

2.4 UAV Survey

Flight plan (Figure 4a) was designed to determine the area and path for the UAV survey (Figure 4b). The UAV was set to enhanced 3D mode. The selected flight height was seventy-five meters with approximately fourteen (14) minutes flight duration using three batteries for an extended area of 160,000 sqm. Duration of both GPS-RTK and UAV survey was a day for an actual area of approximately 50,000sqm.



Figure 4: (a) Flight Plan; and (b) UAV survey

2.5 Data Processing

The RTK-GPS data was downloaded and processed. UAV data was also downloaded and processed using a Photogrammetric and image processing software. GCP coordinates (Figure 5a) were imported into the software for georeferencing (Figure 5b) the orthophotos.




Figure 5: (a) GCP on Orthophoto; and (b) Georeferencing GCP

A dense cloud, mesh textured tiled model was created from which a DTM was generated. The file was exported into a GIS software for digitizing the geometry of the TSF (Figure 6a) and further analysis. Points were picked on the orthophoto to compare with the GPS-RTK validating points as well as the water levels. The digitised geometry of the TSF includes the inner bottom perimeter, the toe perimeter, the top outer and inner edge perimeter. Additional coordinates for spot heights and geometry needed to draw cross-sections across the TSF were extracted on the orthophoto in the GIS software and exported to a Computer Aided Design (CAD) software (Figure 6b). The GPS-RTK coordinates were also imported into the CAD software.




Figure 6: (a) Digitising boundaries of tailings dam; and (b) Point generation in GIS software

All GPS-RTK points and the generated points from the orthophoto were imported into the CAD software. The digitised TSF geometry lines were also imported and refined with imported additional points. The duration of data processing and plotting lasted a day.

3 RESULTS AND ANALYSIS

The orthophoto showing TSF and surroundings in 3D is shown in Figure 7.



Figure 7: (a) Orthophotos of TSF sites (b) 3D projection of TSF

The GPS-RTK coordinates of GCPs used in geo-referencing the orthophoto are shown in the table below (Table 1)

Table 1: Coordinates of GCPs

Number	Eastings	Northings	Elevations	Description
1	775577.529	695909.931	270.400	BGCP1
2	775682.252	695917.161	275.173	BGCP2
3	775725.174	696142.912	268.792	BGCP3
4	775580.103	696208.639	275.536	BGCP4
5	775436.841	696253.518	280.127	BGCP5
6	775467.804	695938.048	271.378	BGCP6

Validating GPS-RTK points compared to the points picked on the processed orthophoto are shown in table 3. From table 3, the highest difference recorded was 4.3cm in elevations and 4.7cm in Eastings.

Table 3: Validating GPS-RTK points compared with Orthophoto points

Description	Coordinates		Difference
	VPGPS1	VPOP1	
Eastings	775579.770	775579.751	0.019
Northings	696209.039	696209.049	0.01
Elevations	275.500	275.543	0.043
	VPGPS2	VPOP2	
Eastings	775682.252	775682.299	0.047
Northings	695917.161	695917.198	0.037
Elevations	275.173	275.142	0.031

Required information was drawn and shown on a standard topographical map with a scale 1:100 (figure 8).





Figure 8: Topographical Map showing TSF geometry and Cross section of TSF

A surface was created from both GPS-RTK points and generated points from the orthophotos in the CAD software. From the triangulation, contours at 5m intervals were generated. Cross sections through each TSF were drawn (figure 8).

4 CONCLUSIONS AND RECOMMENDATIONS

The accuracy of the topographic map was below 5 cm and confirms the suitability of integrating consumer grade UAVs with GPS and GIS for topographical mapping of inaccessible areas in a cost-effective manner. It was cost effective because it took comparatively shorter period for topographical mapping. Field work was drastically reduced. The data was sufficient and accurate enough to design a TSF for sustainable mining activities and investigations. It was also useful for siting piezometers for geotechnical investigations. Consumer grade UAV is recommended for topographical survey especially for inaccessible areas. UAVs are recommended for the production of accurate geometry and cross-sectional drawings for design, geotechnical analysis of slope stability of TSFs.

REFERENCES

- Aleshin, M., Gavrilova, L., & Melnikov, A. (2019). Use of unmanned aerial vehicles on example of Phantom 4 (standard) for creating digital terrain models. *Engineering for Rural Development*, 22, 1686–1692. <https://doi.org/10.22616/ERDev2019.18.N488>
- Attewill, L., Gril, L. S., Penman, J., Vuola, P., Kuusiniemi, R., Maijala, T., Hughes, A. K., Gardiner, K. D., Silva, E. R., & Afonso, J. R. (2004). Long-Term Benefits and Performance of Dams. *13th Conference of the British Dam Society at University of Kent*, 195.
- Brown, A. J., & Hewitt, M. (2016). Managing the safety of very high consequence dams—is the UK doing enough. *Dams—Benefits and Disbenefits; Assets or Liabilities? Proceedings of the 19th Biennial Conference of the British Dam Society Held at Lancaster University from 7–10 September 2016*, 29–41.
- Casagli, N., Frodella, W., Morelli, S., Tofani, V., Ciampalini, A., Intrieri, E., Raspini, F., Rossi, G., Tanteri, L., & Lu, P. (2017). Spaceborne, UAV and ground-based remote sensing techniques for landslide mapping, monitoring and early warning. *Geoenvironmental Disasters*, 4(1), 9.
- Chen, J., Yi, S., Qin, Y., & Wang, X. (2016). Improving estimates of fractional vegetation cover based on UAV in alpine grassland on the Qinghai–Tibetan Plateau. *International Journal of Remote Sensing*, 37(8), 1922–1936.
- Chi, Y.-Y., Lee, Y.-F., & Tsai, S.-E. (2016). Study on high accuracy topographic mapping via uav-based images. *IOP Conference Series: Earth and Environmental Science*, 44(3), 32006.
- Choi, Y., & Song, J. (2016). Sustainable development of abandoned mine areas using renewable energy systems: A case study of the photovoltaic potential assessment at the tailings dam of abandoned Sangdong mine, Korea. *Sustainability*, 8(12), 1320.
- Christiansen, M. P., Laursen, M. S., Jørgensen, R. N., Skovsen, S., & Gislum, R. (2017). Designing and testing a UAV mapping system for agricultural field surveying. *Sensors*, 17(12), 2703.
- Dong, L., Tong, X., Li, X., Zhou, J., Wang, S., & Liu, B. (2019). Some developments and new insights of environmental problems and deep mining strategy for cleaner production in mines. *Journal of Cleaner Production*, 210, 1562–1578.

- Fitzpatrick, B. P. (2015). *Unmanned Aerial Systems for Surveying and Mapping: Cost Comparison of UAS versus Traditional Methods of Data Acquisition*. University of Southern California.
- Ghazal, M., Al Khalil, Y., & Hajjdiab, H. (2015). UAV-based remote sensing for vegetation cover estimation using NDVI imagery and level sets method. *2015 IEEE International Symposium on Signal Processing and Information Technology (ISSPIT)*, 332–337.
- Ghilani, C. D., & Wolf, P. R. (2012). *Elementary Surveying: An Introduction to Geomatics* (13th ed.). Prentice hall.
- Gonzalez, L. F., Montes, G. A., Puig, E., Johnson, S., Mengersen, K., & Gaston, K. J. (2016). Unmanned aerial vehicles (UAVs) and artificial intelligence revolutionizing wildlife monitoring and conservation. *Sensors*, *16*(1), 97.
- Hendriatiningsih, S., Saptari, A. Y., Soedomo, A., Widyastuti, R., Rahmadani, P., & Harpiandi, A. (2019). Large Scale Mapping Using Unmanned Aerial Vehicle (UAV)-Photogrammetry To Accelerate Complete Systematic Land Registration (PTSL)(Case Study: Ciwidey Village, Bandung Regency, Indonesia). *IOP Conference Series: Earth and Environmental Science*, *313*(1), 12042.
- Jalayer, M., Gong, J., Zhou, H., & Grinter, M. (2015). Evaluation of remote sensing technologies for collecting roadside feature data to support highway safety manual implementation. *Journal of Transportation Safety & Security*, *7*(4), 345–357.
- Lato, M. J., Hutchinson, D. J., Gauthier, D., Edwards, T., & Ondercin, M. (2015). Comparison of airborne laser scanning, terrestrial laser scanning, and terrestrial photogrammetry for mapping differential slope change in mountainous terrain. *Canadian Geotechnical Journal*, *52*(2), 129–140.
- Lim, K., Treitz, P., Wulder, M., St-Onge, B., & Flood, M. (2003). LiDAR remote sensing of forest structure. *Progress in Physical Geography*, *27*(1), 88–106.
- Malehmir, A., Socco, L. V., Bastani, M., Krawczyk, C. M., Pfaffhuber, A. A., Miller, R. D., Maurer, H., Frauenfelder, R., Suto, K., & Bazin, S. (2016). Near-surface geophysical characterization of areas prone to natural hazards: a review of the current and perspective on the future. In *Advances in Geophysics* (Vol. 57, pp. 51–146). Elsevier.
- Obanawa, H., & Hayakawa, Y. S. (2015). High-resolution topographic survey using small UAV and SfM-MVS technologies in hardly accessible area. *The International Symposium on Cartography in Internet and Ubiquitous Environment 2015 C*, *4*.
- Pastor, M., Blanc, T., Haddad, B., Drempetic, V., Morles, M. S., Dutto, P., Stickle, M. M., Mira, P., & Merodo, J. A. F. (2015). Depth averaged models for fast landslide propagation: mathematical, rheological and numerical aspects. *Archives of Computational Methods in Engineering*, *22*(1), 67–104.
- Quaye-Ballard, J. A., An, R., Andam-Akorful, S. A., & Quaye-Ballard, N. L. (2013). Role of Geoinformatics for Ghana oil and gas industry. *International Journal on Recent and Innovation Trends in Computing and Communication*, *1*(6), 539 – 546.
- Taddia, Y., Stecchi, F., & Pellegrinelli, A. (2019). USING DJI PHANTOM 4 RTK DRONE FOR TOPOGRAPHIC MAPPING OF COASTAL AREAS. *International Archives of the Photogrammetry, Remote Sensing & Spatial Information Sciences*.
- Tang, L., & Shao, G. (2015). Drone remote sensing for forestry research and practices. *Journal of Forestry Research*, *26*(4), 791–797.
- Terah Antwi, A., Quaye-Ballard, J. A. Arko-Adjei, A., Osei-wusu, W., & Quaye-Ballard, N.

- L. (2020). Comparing Spatial Accessibility and Travel Time Prediction to Commercial Centres by Private and Public Transport: A Case Study of Oforikrom District. *Journal of Advanced Transportation*, 2020, 8. doi.org/10.1155/2020/8319089
- Torgoev, A. (2017). *Assessment of landslide hazard in the environmental hotspot areas of the Kyrgyz Tien-Shan: Spatial analysis and Numeric modelling*. Université de Liège, Liege, Belgique.
- Torres-Sánchez, J., Pena, J. M., de Castro, A. I., & López-Granados, F. (2014). Multi-temporal mapping of the vegetation fraction in early-season wheat fields using images from UAV. *Computers and Electronics in Agriculture*, 103, 104–113.
- Turner, I. L., Harley, M. D., & Drummond, C. D. (2016). UAVs for coastal surveying. *Coastal Engineering*, 114, 19–24.
- Wang, G. (2017). Recent advances in geotechnical engineering of dams and embankments. *Proceedings of the 19th International Conference on Soil Mechanics and Geotechnical Engineering, Seoul*.
- Watanabe, Y., & Kawahara, Y. (2016). UAV photogrammetry for monitoring changes in river topography and vegetation. *Procedia Eng*, 154, 317–325.
- Yakubu, I., Ziggah, Y. Y., & Yeboah, C. (2019). Evaluating Hurst Parameters and Fractal Dimensions of Surveyed Dataset of Tailings Dam Embankment. *International Journal of Geotechnical and Geological Engineering*, 13(4), 217–221.

BIOGRAPHICAL NOTES

Naa Lamkai Quaye-Ballard

Ing. Surv. Mrs. Naa Lamkai Quaye-Ballard is a researcher with interest in sustainable public transportation and geospatial technologies. She is currently a Researcher with the CSIR-Building and Road Research Institute (BRRI), Ghana and pursuing her doctorate degree at KNUST. Having worked as a consulting Geodetic Engineer in Ghana for over fifteen years, she has supervised a lot of projects, notable among them are the construction of the Evans Atta Mills High Street, Accra and Lake Road Interchange, Kumasi. She is an Executive member of Women in Engineering Ghana (WinE). She is a member of the Ghana Institution of Engineering as well as the Ghana Institution of Surveyors. E-mail: naalamkai@gmail.com

Daniel Asenso-Gyambibi

Ing. Surv. Daniel Asenso-Gyambibi is the Director of the CSIR-Building and Road Research Institute, Ghana. His research areas are land administration, GIS and Mapping. He has 23 years work experience, working on a number of projects of national importance including the Ghana Lana Administration Project (LAP), mapping of degraded mine site and reclamation activities, preparation of schemes for urban renewal, perfecting rural land title, hydrographic surveys, mine surveys, GIS in health, transport, mining and agricultural development etc. Daniel's wide experience is as a result of his involvement in projects with varied professionals in the Built Environment. He is a PhD candidate in Geomatic Engineering. He holds an MPhil and BSc in Geomatic Engineering from the Kwame Nkrumah University of Science and Technology, Ghana., Ghana. He is a member of Ghana Institution of Surveyors and Ghana Institution of Engineering.

Jonathan Arthur Quaye-Ballard

Senior Lecturer and Head of Department of Geomatic Engineering, KNUST, Kumasi, Ghana. Holds BSc. Geodetic Engineering from KNUST, Kumasi, Ghana; MSc. Geo-Information Science and Earth Observation from ITC, Enschede, Netherlands; and PhD. Geodesy and Survey Engineering from Hohai University, Nanjing, China. A Licensed Surveyor and member of Ghana Institution of Surveyors (GhIS) and Ghana Institution of Engineering (GhIE). Research interest are Usability Testing; Applications of Geographic Information Systems (GIS) and Remote Sensing (RS) for environmental resource management and analysis; Cartographic Visualization; Systems Analysis; and Computer Supported Collaborative Learning (CSCL). E-mail address: quayeballard.soe@knust.edu.gh

CONTACTS**Ing. Surv. Naa Lamkai Quaye-Ballard**

Council for Scientific and Industrial Research (CSIR) - Building and Road Research Institute (BRRI), P. O. Box UP40 Kumasi, Ghana
Tel. +233 24 4723664
E-mail: naalamkaig@gmail.com

Ing. Surv. Daniel Asenso-Gyambibi

Council for Scientific and Industrial Research (CSIR) - Building and Road Research Institute (BRRI), P. O. Box UP40 Kumasi, Ghana
Tel. +233244255859
E-mail: danasenso@gmail.com

Dr. Jonathan Arthur Quaye-Ballard

Department of Geomatic Engineering, Kwame Nkrumah University of Science and Technology (KNUST). Kumasi, Ghana
Tel. +233 27 7474073
Email: quayeballard.soe@knust.edu.gh
Web site: www.knust.edu.gh