



66

Basic Principle of GNSS Positioning




Basic principle of GNSS positioning

"Positioning" in a 2D space

Positions of points \$1, \$2, and \$3 are known

If the distances from points S1, S2, and S3 to point R are measured, the position of R can be determined.

 ρ_n : Range between point S_n and point R



Basic principle of GNSS positioning


Positioning in the ideal 3D space

Assume:

- 1. Positions of satellites are accurately known
- 2. Clocks on satellites and receiver have no bias
- 3. Signal is transmitted in the vacuum

$$\rho = c * \Delta t$$

ρ: Range between satellite and receiver
c: Speed of signal transmatting in vacuum
Δt: Time difference between satellite and receiver



Orbit and clock variations

Because the system takes measurements based on the speed of light – big number – tiny variations in orbit position and satellite clock time has a big effect on a calculated position on Earth.

The power of the satellite's transmitter can create a pushing force.



The movement of the moon and other bodies have gravitational effects on the satellites.

The systems within the satellite itself have "biases" – delays in time on signals due to the physical creation of the signal within the electronics.

Satellites carry very accurate clocks, but even they will drift a little over time and need to be corrected.

The "pressure" of sunlight on the satellite can push it away from the Sun

The Earth changes shape — Solid Earth Tides — in response to the gravitational pull of the Sun and Moon.

The Earth is not a perfect sphere – it's fatter round the middle and has "lumpy" gravity.

Atmospheric effects

The Troposphere and Ionosphere

The lonosphere is a shell of electrons and electrically charged atoms and molecules that surrounds the Earth. It exists primarily due to ultraviolet radiation from the Sun.

The irregular electron density in the lonosphere can cause phase and amplitude fluctuations in the GNSsignal so degrading its accuracy.

The lonosphere is dispersive – it delays radio of different frequencies by different amounts.

The start of the lonosphere at ~85km
 The Mesosphere and Stratosphere The
 Troposphere up to 18km
 The surface of the Earth

The Troposphere gives the Earth its weather. It's a layer up to 18km thick that contains 75% of the Earth's atmosphere and 99% of the water vapour. It both delays and refracts GNSS signals.


The Troposphere is not ionised – it does not contain free electrons.

The Troposphere is not dispersive – it delays radio of all frequencies by an equal amount.

The Troposphere hydrostatic (dry) delay is caused by dry gases and particles in the troposphere, and it is about 80–90% of the total tropospheric delay. Hydrostatic delay can be precisely determined from surface pressure measurements using empirical models. The tropospheric wet delay is due to water vapor content in the troposphere, and is difficult to precisely model.

Rupert W Brown July 2021

KEY GNSS POSITIONING ERROR SOURCES



Satellite-dependent

- Hardware delays
- Satellite clock biases
- Satellite ephemeris biases

Propagation-dependent

- Ionospheric delay
- Tropospheric delay

Receiver-dependent

- Hardware delays
- Receiver clock biases
- Multipath errors

Difference between RTK and PPP

PPP

$P_r^s = \rho_r^s + c(\delta \tau_r - \delta \tau^s) + T_r^s + I_r^s + d_r + d^s + O^s + \varepsilon_r^s$

All the errors should be carefully corrected or estimated through models or available products (FIN, RAP)

Main differences between RTK and PPP:

1. In terms of error and bias correction method

RTK: use differenced observations PPP: through models and products

2. In terms of timeliness

RTK: real-time


PPP: post-processing

(PPP-RTK can obtain real-time results, but it is not supported in GINAN Version 2)


3. In terms of results

RTK: the derived position is relative to reference station

PPP: independent absolute position



Precise Point Positioning





Introduction of GINAN and CSRS-PPP

Ginan is an open source toolkit for creating precise point positioning (PPP) analysis products, correction streams and positions. It is being actively developed in a Geoscience Australia Positioning Australia program.

CSRS-PPP is an online application for GNSS data post-processing. It uses precise satellite orbit, clock and bias corrections derived from a global network of receivers to determine accurate user positions anywhere on the globe, regardless of proximity to reference stations.

According to Vázquez-Ontiveros, J.R., et al (2023), the CSRS is one of three best PPP processing software in the world. Therefore, we set the CSRS-derived results as benchmark.

Auto-run of GINAN


Developed a Python script for automatic PPP processing using GINAN


```
root@1dac772d269b:/data/scripts# python3 auto_run.py --help
Usage: auto_run.py [OPTIONS]
Options:
                               Station name [required]
  -s. --sta TEXT
                                Start date of the obs to be processed
  -sd, --start_date TEXT
                                [required]
  -ed, --end_date TEXT
                                End date [required]
  -cf, --configure_folder TEXT
                               Path of folder containing configuration files
                                [default: ../configs]
                                Path of folder containing observation files
  -of, --obs folder TEXT
                                [default: ../obs]
  -od, --obs_dateformat TEXT
                                Date formate for the obs files [default:
                                %Y-%m-%d]
  -pf, --pro_folder TEXT
                                Path of folder containing products (SP3, CLK,
                                ERP, BIA) files [default: products/]
  -pp, --pro_provider TEXT
                                Institution name [default: COD]
                                Products type (FIN, RAP, ULT) [default: FIN]
  -pt, --pro_type TEXT
  -t. --template TEXT
                                The yaml template for GINAN processing
                                [default: PPP_template.yaml]
  -m, --ppp mode TEXT
                                PPP processing mode [default: kinematic]
                                Time interval for obs [default: 15]
  -i, --interval INTEGER
  -e, --epochs INTEGER
                                Number of epochs to be processed [default:
                                1440]
  -c, --consellation TEXT
                                Consellations applied in processing [default:
                                GE1
  -y, --yamlfile TEXT
                                Path(name) of derived yaml file [default:
                                out.yaml]
  -on, --out_folder_name TEXT
                                Name of the folder containing derived results
  --help
                                Show this message and exit.
```



Comparison of Kurloo and GA receiver

GINAN Kinematic results







Location: GA

Mode: Kinematic

Date: 06/07/2023 – 22/07/2023

Number of days: 17


Interval: 15s


Obs hours per day: 6h

	Max –	Min (mm)		STD of	f daily me	ans (mm)	STD of (mm)	STD of raw time series (mm)			
	E	N	U	E	N	U	E	N	U		
SYM1	24.0	15.9	46.8	6.1	4.8	16.9	10.7	12.8	35.3		
F9IB00022	49.3	15.2	80.5	14.1	4.4	24.3	25.0	15.9	61.5		

Antenna type on SYM1: TRM59800.00

GINAN Static results







Location: GA Mode: **Static**

Date: 06/07/2023 – 22/07/2023

Number of days: 17


Interval: 15s

Obs hours per day: 6h

	Max –	Min (mm)		STD o	f daily mea	ns (mm)	STD of raw time series (mm)			
	E	N	U	Е	N	U	E	N	U	
SYM1	14.2	11.5	36.5	3.6	2.9	9.0	3.8	2.9	8.9	
F9IB00022	26.7	12.8	56.3	9.0	3.4	14.6	15.0	4.3	19.2	

No phase centre offset and variation corrections for **F9IB00022**

CSRS Static results





Location: GA Mode: **Static**

Date: 06/07/2023 – 22/07/2023

Number of days: 17

Interval: 15s

Obs hours per day: 6h

	Max –	Min (mm)		STD o	f daily mea	ns (mm)	STD of raw time series (mm)			
	E	N	U	Е	N	U	Ε	N	U	
SYM1	14.2	11.5	36.5	3.6	2.8	9.1	3.9	2.9	9.0	
F9IB00022	27.0	30.6	47.5	6.5	6.6	11.6	7.0	7.1	13.4	


No phase centre offset and variation corrections for **F9IB00022**


66


Results analysis for F9IA00012



Kinematic results for F9IA00012







Location: FPE Seawall

Mode: Kinematic

Date: 01/06/2023 – 22/07/2023


Number of days: 52

Interval: 15s

Obs hours per day: 6h

	Max ·	– Min (mr	n)	STD c	of daily me	ans (mm)	STD of	STD of raw time series (mm)			
	Е	N	U	Е	N	U	E	N	U		
GINAN	27.3	11.2	75.8	6.5	3.0	16.1	16.1	11.2	41.8		
CSRS	19.6	19.6	79.0	4.3	4.0	15.6	14.7	13.4	39.6		

Static results for F9IA00012




0.5				CSRS	-PPP statio	F9IA0001	2			
0.4-								And the state of t		The state of the s
0.1-		rmrr	hhh	1		MARA	MM			
0 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7			MAN	THAT .					MANA THE TANK	
-0.3 -0.4										
-0.5	1	i	2	3	1	4	5	<u> </u>	<u> </u>	7
Ü	1		2	,	Epoch/3		5	Ü		, ×
80			1	1		1		1	1	
60 - 6 - 6 - 6 - 6 - 6 - 6 - 6 - 6 - 6 -	ri ^{nguerin} . S		18 18 18 18 18 18 18 18 18 18 18 18 18 1	⁰ ₀₉ 00	energy of	A. 3000	y of Some	18. ₁₆ . 6.16	60000	G
20 - 6-6-0-8)-10-10-10-10			- G-0-0-0-0-0	y. 6. 6. 6. 6. 6	nougherene	e an America	0 · O · O · O · O · O	HONGH ON ONG	@1.0010
0 - -20 - 3 A		/ ⁹ 10	ia. Po _{rtos}					J. 20-44-61-2	Ng.	
1/2	o	p P		ee gegenerd	No.		year ya Tay ya		6.9.9.9.6.	ente de
-40	No product						161			0 0
-60	_ <u></u>									
0	5	10	15	20	25	30	35	40	45	50

	Max ·	– Min (mı	n)	STD o	of daily me	ans (mm)		STD of raw time series (mm) (After convergence)			
	E	N	U	E	N	U	E	N	U		
GINAN	33.0	15.9	44.4	6.5	3.1	12.1	11.2	3.7	12.9		
CSRS	32.4	11.2	60.4	8.2	2.4	13.7	10.5	2.5	13.8		

66

Products comparison: FIN or RAP?







Location: FPE Seawall

Mode: Kinematic

Date: 01/06/2023 - 11/07/2023

Number of days: 40

Interval: 15s

Obs hours per day: 6h

	Max -	– Min (mr	m)	STD o	of daily me	ans	STD of raw time series			
	Ε	N	U	Ε	N	U	E	N	U	
GINAN (FIN)	27.3	11.2	65.6	6.5	2.8	14.5	16.1	11.0	41.5	
GINAN (RAP)	28.2	12.1	60.4	6.5	3.2	15.1	16.8	11.8	43.0	

Station	Location	Date	Processed by	Mode	Products	Max da	ily mean - Mi	in daily mean		STD of daily	means		STD of raw	STD of raw results		
	Location	Date	Trocessed by	Wode	Products	E	N	U	E	N	U	E	N	U		
SYM1	GA CORS	06/07/2023 – 22/07/2023	GINAN	Kinematic	COD_FIN	24.0	15.9	46.8	6.1	4.8	30.6	10.7	12.8	35.3		
		06/07/2023 – 22/07/2024	GINAN	Static	COD_FIN	14.2	11.5	36.5	3.6	2.9	1.7	3.8	2.9	8.9		
		06/07/2023 – 22/07/2025	CSRS	Kinematic	COD_FIN	11.3	12.9	26.7	3.3	3.0	11.5	6.8	6.2	13.3		
		06/07/2023 – 22/07/2023	CSRS	Static	EMR_ULT	14.2	11.5	36.5	3.6	2.8	1.7	3.9	2.9	9.0		
F9I200006	Benchmarking	01/06/2023 - 22/07/2023	GINAN	Kinematic	COD_FIN	72.2	25.6	131.1	14.5	6.1	61.4	30.6	17.6	68.5		
		01/06/2023 - 11/07/2023	GINAN	Kinematic	COD RAP	91.1	28.6	97.9	19.5	6.5	59.9	33.0	18.3	66.3		
		01/06/2023 - 22/07/2023	CSRS	Kinematic	EMR ULT	34.4	20.4	100.6	6.4	4.4	57.1	20.5	18.5	63.7		
		01/06/2023 – 22/07/2023	CSRS	Static	EMR_ULT	31.9	22.9	38.5	6.5	5.7	3.3	7.3	5.9	10.5		
F9IA00012	FPE Seawall	01/06/2023 – 22/07/2023	GINAN	Kinematic	COD_FIN	27.3	11.2	75.8	6.5	3.0	37.8	16.1	11.2	41.8		
		01/06/2023 - 22/07/2023	GINAN	Kinematic	COD RAP	28.2	12.1	60.4	6.5	3.2	39.6	16.8	11.8	43.0		
		01/06/2023 – 22/07/2023	GINAN	Static	COD FIN	34.0	13.5	45.4	6.7	3.3	5.7	11.7	4.1	14.1		
		01/06/2023 - 11/07/2023	GINAN	Static	COD_RAP	27.7	10.9	39.2	5.3	2.7	5.5	10.7	3.4	12.8		
		01/06/2023 - 22/07/2023	CSRS	Kinematic	EMR_ULT	19.6	19.6	79.0	4.3	4.0	35.0	14.7	13.4	39.6		
		01/06/2023 - 22/07/2023	CSRS	Static	EMR_ULT	32.4	11.2	60.4	8.2	2.4	2.3	10.5	2.5	13.8		
F9IA00011	Poatina Power Station		GINAN	Kinematic	COD_FIN	90.4	64.7	222.7	23.9	13.2	66.9	22.0	26.0			
		01/06/2023 – 22/07/2023	GINAN	Kinematic	COD DAD	115.0	43.0	215.3	23.5	10.6	70.3	32.9	26.8	83.4		
		01/06/2023 - 11/07/2023			COD_RAP							30.6	24.1	84.8		
		25/06/2023 – 22/07/2023	GINAN	Static	COD_FIN	62.4	32.8	164.9	17.0	7.9	24.2	23.1	10.8	38.7		
		01/06/2023 - 11/07/2023	GINAN CSRS	Static Kinematic	COD_RAP	72.6 176.1	34.1 338.2	118.2 437.4	13.5 25.5	7.1 47.9	19.6 123.4	18.7	8.6 148.3	33.1 162.0		
		01/06/2023 – 22/07/2023			EMR_ULT							42.9	146.3	162.0		
F9IA00013	Dunstan Drive,Robina	01/06/2023 - 22/07/2023	GINAN	Kinematic	COD_FIN	113.1	94.9	328.3	21.6	20.8	110.5	39.2	39.4	139.5		
		01/06/2023 - 11/07/2023	GINAN	Kinematic	COD_RAP	140.8	113.7	334.1	27.4	23.8	108.3	45.8	43.5	136.9		
		01/06/2023 - 22/07/2023	GINAN	Static	COD_FIN	107.9	93.6	315.2	25.0	20.9	25.2	29.9	21.6	86.9		
		01/06/2023 - 11/07/2023	GINAN	Static	COD_RAP	128.9	74.1	399.8	24.9	20.7	23.8	29.5	21.4	90.7		
		01/06/2023 - 22/07/2023	CSRS	Kinematic	EMR_ULT	150.2	75.4	435.2	39.9	18.9	137.1	102.2	55.8	162.7		
		01/06/2023 - 22/07/2024	CSRS	Static	EMR_ULT	66.0	38.9	123.4	15.4	7.9	14.3	16.4	8.7	31.6		
F9IA00016	Toowoomba Bypass	15/06/2023 - 22/07/2023	GINAN	Kinematic	COD_FIN	47.4	21.1	70.1	11.7	5.8	54.6	35.6	17.9	59.7		
		17/06/2023 - 10/07/2023	GINAN	Kinematic	COD_RAP	40.0	20.5	84.1	9.8	6.1	62.8	34.4	17.1	77.4		
		15/06/2023 - 22/07/2023	GINAN	Static	COD_FIN	28.2	19.2	55.4	6.9	5.2	6.5	14.3	5.7	13.4		
		15/06/2023 - 21/07/2023	GINAN	Static	COD_RAP	28.2	19.2	55.4	7.0	5.2	6.4	14.3	5.7	13.5		
		15/06/2023 - 22/07/2023	CSRS	Kinematic	EMR_ULT	140.3	51.2	80.1	29.3	10.7	46.6	69.7	28.2	54.6		
		15/06/2023 - 22/07/2023	CSRS	Static	EMR_ULT	44.5	12.5	46.9	11.6	3.6	4.2	14.6	3.7	13.3		
F9IB00022	GA Benchmark	05/07/2023 - 22/07/2023	GINAN	Kinematic	COD_FIN	49.3	15.2	80.5	14.1	4.4	55.9	25.0	15.9	61.5		
		05/07/2023 - 09/07/2023	GINAN	Kinematic	COD_RAP	41.2	12.9	67.4	18.2	5.4	70.5	27.1	15.0	75.4		
		05/07/2023 - 22/07/2023	GINAN	Static	COD_FIN	26.7	12.8	56.3	9.0	3.4	11.8	15.0	4.3	19.2		
		05/07/2023 - 22/07/2023	GINAN	Static	COD_RAP	20.2	10.6	31.6	9.7	4.4	10.3	4.0	4.7	15.9		
		05/07/2023 - 05/07/2023	CSRS	Kinematic	EMR_ULT	17.3	14.4	33.6	3.9	4.0	26.6	12.6	13.4	28.1		
		05/07/2023 – 22/07/2023	CSRS	Static	EMR_ULT	27	30.6	47.5	6.5	6.6	3.5	7.0	7.1	13.4		
F9IB00023	Toowoomba Bypass	01/06/2022 22/07/2022	GINAN	Kinematic	COD_FIN	89.6	27.0	45.2	15.1	6.3	51.5	20.1	14.4	E2 0		
		01/06/2023 - 22/07/2023 01/06/2023 - 11/07/2023	GINAN	Vinomatic	COD BAD	78.3	25.8	63.2	14.1	6.4	53.2	29.1 27.2	14.4 14.9	53.8 56.8		
			GINAN	Kinematic	COD_RAP											
		01/06/2023 - 22/07/2023	GINAN	Static	COD_FIN	44.2	19.6 15.0	36.7	8.9	4.9	6.8	14.4	5.4	11.2		
		01/06/2023 - 11/07/2023		Static	COD_RAP	46.2	15.0	37.9	9.8	4.1	7.6	15.2	4.5	12.2		
		01/06/2023 - 22/07/2023 01/06/2023 - 22/07/2023	CSRS CSRS	Kinematic Static	EMR_ULT EMR_ULT	77.8 50.7	55.7 12.7	72.1 45.8	15.5 11.6	9.0 3.2	45.7 4.6	33.9 13.2	24.3 3.5	59.3 13.6		
F0100000		01/00/2023 - 22/0//2023										13.2	J.J	13.0		
F9IB00027	Mt Bogong	01/06/2023 - 22/07/2023	GINAN	Kinematic	COD_FIN	152.7	128.9	351.7	32.4	25.9	93.4	44.4	38.9	118.2		
		01/06/2023 - 11/07/2023	GINAN	Kinematic	COD_RAP	139.8	111.5	272.3	30.0	23.8	95.7	41.5	37.1	122.4		
		01/06/2023 - 22/07/2023	GINAN	Static	COD_FIN	220.5	130.7	229.3	34.2	21.4	30.3	41.6	24.3	67.5		
		01/06/2023 - 11/07/2023	GINAN	Static	COD_RAP	117.3	71.1	208.7	29.0	16.2	32.4	35.5	20.7	66.4		
		01/06/2023 - 22/07/2023	CSRS	Kinematic	EMR_ULT	103.7	193.5	602.8	21.0	27.2	143.5	87.4	130.7	261.7		
		01/06/2023 - 22/07/2023	CSRS	Static	EMR_ULT	64.1	46.1	142.2	18.7	9.7	19.1	19.6	11.2	41.3		


Fundamental Role of Reference Station

- Enable the accurate positioning of points on the earths surface
- Direct connect to specifical Reference Frames, Nationally and Globally
- The importance of Geospatial Reference Systems was recognised by the United Nations in 2015 adoption of a General Assembly Resolution promoting the importance of an accurate, sustainable and accessible Global Reference Frame to support science and society (Nicholas Brown, 2019)
- Well defined and realised station coordinates (and velocities) underpin science of the Earth's interior, solid Earth, atmosphere, oceans, space environment (John Dawson, 2019)
- The stability of its reference station is crucial to obtain accurate and reliable monitoring results (Guanwen Huang, 2023)





What if the reference station is not stable?







What if you don't have a reference station?







Conclusions

- 1. Kurloo receiver demonstrates a remarkable PPP precision, achieving 1.5, 1.5, and 4.0 cm in kinematic mode, and 1.0, 1.0, and 1.5 cm in static mode on E, N, and U directions. (Based on the results of F9IA00012)
- 2. GINAN is capable of achieving comparable PPP precision to CSRS, although in certain stations, the results derived from CSRS show better precision.
- 3. The results obtained from rapid-products and final-products exhibit comparable positioning precision.
- 4. Despite utilizing the same receivers across different stations, their positioning performance varies. The reason need to be investigated.
- 5. Using the combination of GPS and Galileo constellations for GINAN PPP processing can achieve better PPP performance.









www.kurloo.io

Kurloo Technology Pty Ltd

Designed and Made in Australia 24 Finchley St, Milton, 4064

Queensland, Australia

ABN 85 654 669 342

To request further information or book an appointment:

Email: sales @kurloo.io

Or contact

Amy Hooper

Sales Manager

amy.hooper@kurloo.io