www.ngs.noaa.gov



# Recent IERS Site Survey of Multiple Co-located Geodetic Techniques by NGS

Kendall Fancher, <u>Dru Smith</u>, Steve Breidenbach, Jeff Olsen, Nagendra Paudel

NOAA's National Geodetic Survey, U.S.A.

4/14/2010

FIG 2010 General Assembly

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

## Outline

- Relation between national datums and ITRF
- Need for co-location site surveys
- GGAO survey by NGS
- Future activities

4/14/2010

www.ngs.noaa.gov

#### National datums and the ITRF

- 2-D Horizontal datum?
  - 3-D Geometric Reference System!
- Many countries adopt a frame tied to ITRF
  - USA:



4/14/2010

FIG 2010 General Assembly

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

#### Reliance on IERS

- National Geodetic Authorities:
  - Define national reference systems (datums)
  - Have resources
  - Rely on IERS to provide the ITRF
- IERS
  - Updates the ITRF
  - Is a voluntary international organization

4/14/2010

www.ngs.noaa.gov

#### Resources vs. Reliance

• My recent pitch to NGS policy makers:

"It is the duty of those agencies with both resources and a reliance on ITRF to apply some of those resources to the improvement and maintenance of the ITRF"

Currently in NGS policy debate for 2010

4/14/2010

FIG 2010 General Assembly

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

## Co-location Site Surveys

- ITRF realizations are the combination of four space geodetic techniques
  - VLBI, SLR, GNSS, DORIS
  - Each contributes differently to ITRF
  - <u>Co-locating these techniques allows for their combination</u>.
  - Examples of co-location:
    - Space (SLR reflectors on GNSS satellites)
    - Ground (GNSS antennas near VLBI antennas)


4/14/2010


www.ngs.noaa.gov


#### Ground co-location

- Antennas "near" one another is not enough
- Must know 3-D geometric vector from ERP to ERP\*
  - \* Electronic Reference Point
- Co-location surveys only yield PRP to PRP\*
   \*Physical Reference Point

4/14/2010









www.ngs.noaa.gov


# **GGAO** Survey

- Anticipating a policy shift, NGS engaged in retraining employees in co-location survey techniques
  - Goddard Geophysical and Astronomical Observatory, Maryland, U.S.A.
  - PRP-to-PRP only

4/14/2010







• GPS

- Trimble R7 GNSS receivers

- Javad Ringant-DM GNSS antenna

• Leveling

- Leica DNA03 digital level

- 2-meter Invar staff

• Angles and Distances

- Leica TDMA 5005 total station

- Leica GPH1P precision reflectors

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

# Status of GGAO Project

- GPS data analysis completed
- Tie vector data analysis is near completion
- A project report will be delivered to the IERS in the format proposed by the IERS Site Survey and Co-location Working Group

4/14/2010

www.ngs.noaa.gov

#### **NGS Future Work**

- Planning other IERS site surveys
  - Brewster (Washington State, USA, VLBI/GNSS)
     planned for 2010
- Debating total resource allocation for future years
- Engaged in IERS Site Survey and Co-location Working Group

4/14/2010

FIG 2010 General Assembly

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

#### **NGS Future Work**

- Evaluating external software (Sarti, Johnston) for future operational use
- Training additional employees on site survey techniques

4/14/2010

www.ngs.noaa.gov

## FIG Future Work

- Efficiency is gained if the IERS has site surveys performed by local persons at local sites
  - Think globally, act locally
- NGS will likely work with other international agencies to develop training and workshops to encourage more international participation on IERS site surveys...we all benefit!

4/14/2010

NOAA's National Geodetic Survey Positioning America for the Future www.ngs.noaa.gov		www.ngs.noaa.gov
	Questions?	
4/14/2010	FIG 2010 General Assembly	